

EXACT-V2

DualCast ATSC 1.0 / 3.0 Digital TV Exciter

The EXACT-V2 is the next generation, compact and powerful exciter platform that delivers an ATSC compliant, on-channel output as well as performs adaptive RF precorrection for the best possible broadcast signal.



Hitachi-Comark provides high performance and award-winning television transmitters that are backed by more than 40 years of leadership in both inductive output tube (IOT) and solid-state broadcast technologies.

The next generation EXACT-V2 Digital TV Exciter was developed for the ATSC broadcast market. It uses the compact 1RU exciter hardware platform in conjunction with ATSC compatible firmware and software. The EXACT-V2 exciter is designed to work either in a stand-alone mode with OEM DTV transmitters or fully integrated in Hitachi-Comark digital TV transmitters.

Flexibility by Design

The EXACT-V2 exciter's core modulation and correction functions are processed by firmware that resides on internal Field Programmable Gate Arrays (FPGA).

This architecture provides flexibility so as digital TV standards evolve and change, the processing can be upgraded and adapted to meet these new requirements, simply by loading new firmware.

Beyond the FPGA technology, the exciter platform incorporates a microcontroller for user interface to the monitor and control functions. Custom software running in the exciter provides user access through various Man-Machine Interfaces (MMI) provided from the EXACT-V2.

DAP Technology Streamlines Performance

The EXACT-V2 exciter integrates Digital Adaptive Precorrection (DAP) technology, which provides superior performance that is unattainable using any other correction technique.

This technology allows for simple and easy setup and maintenance of a high-performance transmitter system.

DAP technology provides unsurpassed digital correction of all distortions created by a DTV transmitter system. These distortions include nonlinear distortions created by active amplifier devices, such as amplitude and phase distortions along with correction for memory effect. Additionally, DAP corrects linear distortions created by the transmitter's high-power passive RF system, such as group delay and frequency response distortions maximizing the SNR performance.

Advanced Monitoring & Control

The EXACT-V2 exciter incorporates local control and monitoring using an enhanced user interface front panel with backlit LCD display, LEDs, and menu driven push buttons. Local access includes menus for initial setup, configuration status, and control functions. The front panel displays the forward & reflected power levels, output RF shoulders as well as the SNR performance.

KEY FEATURES

- ▶ Unique *DualCast* ATSC 1.0 to 3.0 upgradeable, protects investment*
- ▶ New IP optimized platform (7xGbe ports) specifically for ATSC 3.0
- ▶ Optional SNMP client, activated via software license
- ▶ User friendly but advanced WEB GUI local or remote control
- ▶ *Industry Leading* Digital Adaptive Precorrection (DAP)
- ▶ Dual TS inputs (SMPTE-310M or ASI), provides seamless A/B input redundancy
- ▶ Compact 1RU platform, stand alone operation
- ▶ Embedded forward and reflected RF power measurements
- ▶ SNR, shoulders, and FWD / RFL power monitoring via front panel

The EXACT-V2 exciter can also be remotely controlled using the Web GUI interface with nothing more than a PC running a standard web browser. The Web GUI allows users to retrieve information such as SNR, lower and upper RF shoulder measurements, user configuration, and alarms.

ATSC Now and the Future

The EXACT-V2 is fully compliant with the ATSC 1.0 A/53 DTV standard. EXACT-V2 includes powerful processing and the required can also be field upgraded* with new firmware/software to support ATSC 3.0, preserving your investment.

Seamless TS Input Switching

The EXACT-V2 features two independent sets of dual (A & B) transport stream (TS) inputs. The dual TS inputs allow signal path diversity (i.e. one ASI TS feed via a fiber link and a second ASI TS feed via a STL microwave). The A & B TS switching can be set for automatic or manual depending on the user's preference.



Monitor/Control:

- ✓ The EXACT-V2 includes a built-in Web based user monitor and control interface
- ✓ Pertinent information is displayed in a user friendly and very intuitive layout
- ✓ The exciter can be setup in minutes with dedicated menus for operation and control

SPECIFICATIONS

Operating Frequency:

- VHF Band 1; 54-88MHz
- VHF Band 3; 174-216MHz
- UHF Bands 4 & 5; 470-862 MHz

Modulation / Standard:

- ATSC 1.0 8VSB ~ ATSC A/53
- ATSC 3.0 ready ~ ATSC A/300*

ASI Interfaces (ATSC 1.0):

- 2 inputs, 1 output; DVB-ASI (or SMPTE-310M input)
- ASI = BNC female connector, 75Ω
- Auto switching between ASI ports

Gbe Interfaces (ATSC 3.0):

- 4 x Gigabit Ethernet; RJ45 ports
- Protocols: UDP, IP, IGMP (V2&V3)
- STL Interface (A/324)

RF Output:

- 0dBm output power (rms),
- +14dBm output (rms) (opt.)
- N female connector, 50Ω
- Low level rear panel RF monitor port, SMA 50Ω @ -20dBm
- 6 MHz RF channel bandwidth
- > 37dB global MER

Clock and Synchronization:

- 1PPS in/out, BNC female 50Ω,
- 10MHz in/out, BNC female 50Ω

Ancillary Inputs:

- ALE / NLC RF correction inputs, -15 to -5dBm level, SMA female
- FWD/RFL power monitoring inputs, 5dBm max level, SMA

Monitor/Control:

- Web: 3 x Gigabit Ethernet, RJ45
- SNMP: Gigabit Ethernet, RJ45 (opt.)
- General Purpose IO, DB-9 x2
- GPS input, BNC 50Ω (external antenna optional)

Environmental & Safety:

- 0° to 50° C Temp range
- ≤ 95% non-condensing relative humidity

General Electrical & Mechanical:

- 19" W x 1.75" H x 10" D
- 110 ~ 240 VAC, 50/60 Hz, 70 watts
- 4.5 kg (net) / 10 lbs.
- > 0.9 power factor
- Air cooled, right to left air flow



EXACT-V2 Rear Panel

* Requires purchase of optional licenses

ORDERING INFORMATION

Please contact your authorized Hitachi-Comark representative.
 US Sales 1-800-288-8364 or 413-998-1100
 Hitachi Kokusai Electric Comark LLC
 104 Feeding Hills Road
 Southwick, MA 01077

Hitachi Kokusai Electric Comark LLC. All rights reserved. Hitachi-Comark strives to present accurate product data but reserves the right to change specifications without prior notice. The ATSC product line specifications in this brochure are current as of the publication date listed below. Please verify product specifications by contacting our office. COMARK™ products, features and technology may be covered by one or more U.S. or foreign patents.

www.comarktv.com

- EXACT-SNMP → Optional SNMP License
- EXACT-TS over IP → Optional TS over IP License (1.0)
- EXACT-14DB → Optional +14dBm Output
- EXACT-A3UP → Upgrade ATSC 3.0 License (8x PLPs)
- EXACT-LDM → Upgrade ATSC 3.0 LDM