


1 2 )  
- 3 - 3 / 3 4

5

! ( # :  
\$ % % & \$ ' ( & ! ) \* \$ , % & + )  
/ ' ' ( & ) - \* + ' % % & . , ( & % & ' \$ ! )  
! " # \$ % & ' ( ) \* + , - . / : ;  
! " # \$ % & ' ( ) \* + , - . / : ;  
( ) ( \$ ) \* '+  
) , - \$ / 0 1 2 0 1 /  
, 5 % ' ' 3 4 , \$ 6 / \$



# UHF Digital TV Transmitters

## E-Compact TV - High Efficiency - Air Cooling - High Power

### GENERAL FEATURES

- IP Input;
- Modular power amplifiers;
- High efficiency with Doherty Technology;
- Air Cooling;
- Automatic Fan Speed Control: low noise levels, energy saving and increased lifespan;
- Power Supply with Power Factor Correction  $\geq 0.9$ ;
- Measurements and Alarms through front display and keyboard or via web;
- VSWR and Overdrive protection via hardware with power reduction;
- Overheating protection via software for the internal modules;
- Automatic Digital Pre-correction (Linear and No-Linear);
- Telemetry: WEB Server/SNMP, for local or remote management;
- AGING transistor compensation via exciter front panel;
- Automatic GM compensation with temperature;
- Gain and Phase adjustments per drawer;
- SFN Operation;
- Isolated combiner, enabling Hot Swap<sup>4</sup>

### INCLUDED:

General Control Software, WEB Server and SNMP;  
USB communication Drivers;  
PT-BR, US-EN or ESP manuals (digital formats).

### OPTIONALS:<sup>5</sup>

- Telemetry through GPRS interface;
- Exciter Redundancy;
- Measurement Software;
- Time base by GPS, inside the exciter;
- Terrestrial reception for UHF retransmission (connector N female);
- Satellite reception (DVB-S/S2) for UHF retransmission (connector F female);
- Conditional Access Module with up to four simultaneous services, and display of up to eight services;<sup>6</sup>
- Channel filter;
- Low-pass filter and after filter RF sample.

Communication Interfaces	USB / Ethernet <sup>2</sup> / SNMP
Frequency Stability	$\pm 1$ Hz (internal GPS)
Oscillator	PLL synthesized
Power Factor	better than 0.9
Operation Altitude	up to 2,500m a.s.l. <sup>7</sup>
Environment temperature range	from 0°C to +45°C
Environmental Humidity range	from 0 to 95% (non-condensing)

### BTS, TS or IP INPUTS

Formats	DVB-ASI 188 / 204 bytes Ethernet <sup>2</sup> (IEEE 802.3u) 10Base-T/100Base-TX
Connectors	BNC-Female RJ45
Impedance	75 $\Omega$

### OUTPUT

Operation Frequency	470MHz to 806MHz (UHF)
Bandwidth	6 / 7 / 8 MHz
Power	up to 9.5kW <sub>rms</sub> before filter
Minimum Operation Power (after filter)	10% of nominal power (increased in steps of 10W) <sup>8</sup>
TV Standard	ISDB-T, ATSC and DVB-T2
Intermodulation	-50dB @ $\pm 3.15$ MHz (BW=6MHz) <sup>5</sup> -50dB @ $\pm 4.2$ MHz (BW=8MHz)
Harmonics / spurious	better than -60dBc
MER	34dB to 38dB

### TECHNICAL TABLE (typical values)

Model	EC701HP		EC702HP		EC703HP		EC704HP		EC706HP		EC708HP		EC712HP	
Output Power (W) <sup>9</sup>	B.F. <sup>10</sup>	A.F. <sup>10</sup>	B.F. <sup>10</sup>	A.F. <sup>10</sup>	B.F. <sup>10</sup>	A.F. <sup>10</sup>	B.F. <sup>10</sup>	A.F. <sup>10</sup>	B.F. <sup>10</sup>	A.F. <sup>10</sup>	B.F. <sup>10</sup>	A.F. <sup>10</sup>	B.F. <sup>10</sup>	A.F. <sup>10</sup>
ATSC	800	700	1,600	1,400	2,400	2,100	3,200	2,900	4,800	4,200	6,500	5,600	9,500	8,500
DVB-T2	750	600	1,500	1,300	2,200	1,900	3,000	2,600	4,500	3,900	6,000	5,200	8,800	7,700
ISDB-T	700	580	1,400	1,200	2,100	1,800	2,700	2,400	4,000	3,600	5,400	4,800	7,800	7,000
AC Mains (43 to 63Hz)	M220 B220		M220 B220 T220 T380		M220 B220 T220 T380		M220 B220 T220 T380		M220 B220 T220 T380		M220 <sup>11</sup> B220 <sup>11</sup> T220 T380		M220 <sup>11</sup> B220 <sup>11</sup> T220 T380	
Output Connector	EIA 1-5/8"		EIA 1-5/8"		EIA 1-5/8"		EIA 1-5/8"		EIA 3-1/8"		EIA 3-1/8"		EIA 3-1/8"	
PA Modules	1 module		2 module		3 module		4 module		6 module		8 module		12 module	
Typical AC Consumption(W) <sup>9</sup>	ATSC 2,055		4,009		5,964		7,918		11,827		15,736		23,575	
	DVB-T2 2,051		4,002		5,954		7,905		11,807		15,710		23,515	
	ISDB-T 1,935		3,810		5,685		7,560		11,310		15,060		22,620	
Typical Heat Dissipation (BTU/h) <sup>9</sup>	ATSC 4,539		8,551		12,656		16,618		25,111		33,600		50,983	
	DVB-T2 4,857		9,058		13,320		17,647		26,773		35,584		53,206	
	ISDB-T 4,595		8,688		12,840		17,052		25,921		34,060		51,840	
Rack dimensions (RU)	8		25		25		25		40		40		40	
Number of Racks	1		1		1		1		1		1		2	
Rack total width (mm)	570		570		570		570		570		570		1,140	
Rack total depth (mm)	900		1,100		1,100		1,100		1,100		1,100		1,100	
Transmitter weight (kg)	70		170		210		250		350		420		700	

### Remarks / Notes

- <sup>1</sup> Except EC712HP.
- <sup>2</sup> Ethernet is a registered trademark of Xerox Corporation
- <sup>3</sup> Except EC701HP.
- <sup>4</sup> The PA modules can be removed / inserted with the transmitter in operation, although the PA being removed / inserted must be switched off.
- <sup>5</sup> Contact Hitachi Kokusai Linear for optionals availability in each standard.
- <sup>6</sup> DVB-CA Standard (conditional access)  
- DVB Common-Interface (DVB-CI) Module card of type PCMCIA CAM (Irdeto systems, Conax)  
Card and jacket not included.
- <sup>7</sup> Altitudes above 2,500m under consultation.  
a.s.l.: above sea level.
- <sup>8</sup> Except for model EC701HP, nominal power of 580W, in which the minimum power is 50W.
- <sup>9</sup> May change depending on MER value, channel and output power. For details, consult Hitachi Kokusai Linear.
- <sup>10</sup> B.F.: Before Filter / A.F.: After Filter
- <sup>11</sup> Under consultation.

### Hitachi Kokusai Linear Equipamentos Eletrônicos S/A.

#### Headquarters

Rodovia BR 459, n° 121-A, Km 121 - Bairro Corrêgo Raso  
37540-000 - Santa Rita do Sapucaí - MG - Brazil  
Phone: +55(35) 3473-3473 Fax: +55 (35) 3473-2425  
www.hitachi-linear.com.br

#### Commercial Office - São Paulo

Alameda Santos, 745 - Conj 92 - Cerqueira César  
01419-001 - São Paulo - SP - Brazil  
Phone: +55(11) 3541-3244 Fax: +55(11) 3541-2425

#### Comark Office

104 Feeding Hills Rd, Southwick, MA 01077 - USA  
Phone: (413) 998-1100 Fax: (413) 998-1194